SC 1332 AIR CONDITIONER

Product data sheet 2010

Product range	split unit air conditioners
Brand name	Zibro
Model	SC 1332
Colour	Zibro white
EAN code indoor unit	8713508752440
EAN code outdoor unit	8713508752457

Technical specifications

		Cooling	Heating
EER / COP *	W/W	3.23	3.60
EE-Class / Heating performance *		A	A
Capacity * (nom.)	kW	3.2	3.2
Power consumption (nom.)	kW	0.99	0.89
Power supply	V/Hz/Ph	230~ / 50 / 1	
Current **	A	4.6	
Air flow (min-max.) **	m^3/h	400 - 580	
For rooms up to **	m^3	80 - 100	
Dehumidification capacity ***	L/24 h	26	
Operating range	°C	-15 - 43	
Thermostatic range	°C	17 - 30	
Sound pressure level indoor**	dB(A)	35 - 41	
Sound pressure level outdoor**	dB(A)	54	
Fan speed		3 positions	
Control		electronic / remote	
Air filter	type	Screen/active carbon/3M HAF	
Refrigerant type / charge	R / gr	R410A / 790	
Max. length refr. pipe between in- / outdoor unit ****	m	4	
Max. diff. in height between in- / outdoor unit ****	m	2	
Dimensions indoor (w x h x d)	mm	790x275x190	
Dimensions outdoor (w x h x d)	mm	780x540x250	
Compressor type		rotary	
Protection class indoor	IP	IP 20	
Protection class outdoor	IP	IP 24	
Weight indoor	kg	14	
Weight outdoor	kg	26	
Guarantee	years	2	

* *Measured conform EN 14511-2007*

** *To be used as indication*

*** *Moisture removal at 32°C, 80% RH*

CE guarantee 2 YEARS



20 ft = ...
40 ft = tbc
HQ = tbc



W x D x H =
in: tbc
out: tbc

Gross =
tbc kg/
tbc kg

Accessories

Remote control (ABS 10FP)	8713508752587
Remote control holder	
2 pcs. AAA batteries	
4 metres drainage tube	
User manual	D DK NL E N F PL FIN S GB SLO I TR
Installation manual	D E F GB NL PL
Quick Installation Guide	

Most important spare parts

Spare part description	EAN Code

zibro®
home made climates

SC 1332 AIR CONDITIONER



3-layer fi lter, anti-allergy

Prevents the room temperature from fal-ling below 8 °C

Easy installation via Quick Connector sys-tem

Extra frost protection in outdoor unit

Features

Cooling + dehumidifying + heating (heat pump): The air conditioning is a complete air treatment system. It can cool, dehumidify and heat the air.

Air conditioning: In COOLING mode the unit produces a pleasant and refreshing cool airflow.

Heating: In HEATING mode the unit produces a warm and comfortable airflow. Because also the free of charge energy from the outdoor air is used the efficiency of the system can reach up to 340%!

Dehumidifying: In DRY mode the unit dehumidifies the air in the room as efficient as possible. Note: In COOLING mode the air is also dehumidified.

Easy installation via industial proven "Spanner"Quick Connector System: The air conditioner is provided with a Spanner type Quick connection system which makes it easy to connect indoor unit with outdoor unit, simply pull the lever without the need for tools. There is no need for additional brazing anymore. The Spanner type Quick connector is of the Parker brand, ensuring the most durable and high quality quick connection method. The Parker Quick Connector has proven quality in industrial applications.

Connection via flexible tubes: The air conditioner is provided with Stainless Steel flexible refrigerant gas line and Soft Copper refrigerant liquid line. Due to these flexible lines the installation can be done in the most easiest way without the risk of folding/ cracking.

EXTRA: frost protection in outdoor unit: The outdoor unit is provided with a PTC heating cable. When the system is working as a heater in the wintertime the PTC heating cable will keep the drip pan in the outdoor unit clear of ice, making sure the condensate water can reach the drain point. Furthermore also the compressor crankcase is provided with a heating cable. Ensuring the unit can perform and start up at extreme wheather conditions.

EXTRA: Home Freezing prevention Button: Upon pressing this button the unit will go into the freezing prevention mode. The unit will overrule the indoor temperature setting and set it to approx 8-10°C. In this way preventing your home from freezing during cold periods at the lowest possible energy consumption. When this mode is selected the indoor unit display will show "FP". This button can only be operated in heating mode.

Environment friendly refrigerant R410A: The most preferred and environmental friendly refrigerant R410a is used in the air conditioner.

Turbo mode: With the Turbo mode the air conditioner will reach the preset temperature in the shortest possible time.

3-layer air filter: The air conditioner is equipped with a 3 layer filter package to clean the circulated room air. The 3M™ HAF air filter delivered together with this unit captures allergens like bacteria, dust and pollen from the circulated air with an efficiency up to 80%. Pollen are well known as an important stimulus for hay-fever allergy. The active carbon filter removes unpleasant odours from the air and the screen filter captures large dust particles. The screen filter can be cleaned with a vacuum cleaner and/or lukewarm water. Per season 2 to 3, 3M™ HAF and active carbon filters will be used. These filters are available in a consumer package (including 1 3M™ HAF and 1 active carbon filter).

Remote control with LCD screen: The unit can be operated with an easy to handle remote control including LCD-display. Using the remote control the air conditioner can be operated up to a distance of approx. 8 metres.

Remote control holder: The remote control can be placed in the wall mounted remote control holder which is delivered together with the unit.

Adjustable airflow: The up-down airflow can be automatically changed by using the SWING mode. The left-right airflow can be changed manually.

Sleep Mode: This function enables the air conditioner to increase (cooling) or decrease (heating) automatically 1°C per hour for the first two hours and then maintain the same temperature for five hours after which the air conditioner will stop operating automatically. It maintains the most comfortable temperature and saves energy at the same time.

Fan speed setting: Select with FAN speed button: Automatic, Low, Medium or High. The LCD display on the remote control will show the chosen speed.

Automatic operation: The air conditioning system can be set to automatic operation for the most suitable MODE: Cooling, Dehumidifying or Heating, monitoring the indoor temperature.

Auto restart function: If there is any power failure during operation, the operation status before power failure is memorised and the unit starts operating automatically after power recovery.

Timer: Use TIMER or set a working time between 30 minutes and 24 hours. The preset time appears in the display of the remote control. The unit switches ON or OFF automatically when this time is passed.

Full colour box: The unit is delivered completely with all auxiliary parts in a full colour box showing application and operation information in 13 languages.